

ASSEMBLY INSTRUCTION

SKU# 518001

NOTE: Please consult a qualified electrician if you are not certain of the installation.

CAUTION: Before starting the installation or service, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

1. Carefully unpack the fixture, lay out all parts on a clean surface.
2. Attach the mounting strap to outlet box using the outlet box screws provided.
3. Weave the fixture wires up through the tube D, through the tube C, through the tube B, through the tube A, through the bushing on the canopy.
4. Fasten tube D onto the nipple E, tube C onto the nipple D, tube B onto the nipple C, tube A onto the nipple B, and fasten nipple A into the bushing.
5. Connect ground wire from fixture to ground wire from supply circuit. Connect white wire from fixture to white wire (neutral wire) from supply circuit. Connect black wire from fixture to black wire (live wire) from supply circuit. Cover the connectors using the provided wire connectors. Position wires back inside outlet box.
6. Place the canopy against the outlet box by aligning the protruding mounting screws all the way through the canopy and tighten lock nuts to mounting screws until the fixture body was held firmly against ceiling.
7. Unscrew the socket ring from the socket. Place shade over socket, and reattach socket ring to socket to secure shade.
8. Install the bulb (sold separately).
9. Reconnect the power.

